

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau(43) International Publication Date
17 July 2003 (17.07.2003)

PCT

(10) International Publication Number
WO 03/058835 A1(51) International Patent Classification⁷: H04B 1/59

(21) International Application Number: PCT/NO03/00004

(22) International Filing Date: 9 January 2003 (09.01.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
20020112 9 January 2002 (09.01.2002) NO

(71) Applicant and

(72) Inventor: VAVIK, Geir, Monsen [NO/NO]; Kirkhaugen, Øvre Vikeraunet, N-7057 Jonsvatnet (NO).

(74) Agent: BRYN AARFLOT AS; P.O.Box 449 Sentrum, N-0104 Oslo (NO).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,

CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: ANALOGUE REGENERATIVE TRANSPONDERS, INCLUDING REGENERATIVE TRANSPONDER SYSTEMS



(57) Abstract: In a transponder (19) for amplification of a received signal (60) into an antenna (1), to a signal (61) for retransmission, and where the retransmitted signal (61) possibly may have information superimposed, a quenched oscillator (5) is incorporated as amplifying element. The oscillator (5) is preferably of superregenerative type and exhibits negative resistance (30) for the received signal (60). Transponders according to the present invention may be introduced as system elements in a wireless or wire based network to work as intelligent or unintelligent connections in the network. The transponders can also be used in positioning systems.